

Sub 7  
1. (Amended) A device for attaching a suction cup to a fixture, the suction cup having a compressible head attached to a neck, the neck attached to an engagement member, said device comprising:

a first pair of horizontal, generally parallel, rigid wires;

YB2  
a second pair of rigid wires, each wire of said second pair of rigid wires transverses and engages each wire of said first pair of rigid wires defining a generally rectangular opening for receiving the head and for retaining the neck in said opening; and

~~a fastener arrangement for fastening said device to the fixture.~~

503  
11. (Amended) An assembly comprising:

a first pair of horizontal, generally parallel, rigid wires;

YB3  
a second pair of rigid wires, each wire of said second pair of rigid wires transverses and engages each wire of said first pair of rigid wires defining a generally rectangular opening for receiving the head and for retaining the neck in said opening; and

a fastener arrangement for fastening said assembly to a fixture; and

a suction cup having a compressible head attached to a neck, the neck attached to an engagement member, said head being insertable into said opening and said neck being retainable in said opening.

YB4  
21. (New) A fixture having a device for attaching a suction cup to the fixture, the suction cup having a head attached to a neck, the neck attached to an engagement member, said device comprising:

a first pair of horizontal, generally parallel, rigid wires; and

a second pair of rigid wires, each wire of said second pair of rigid wires transverses and engages each wire of said first pair of rigid wires defining a generally rectangular opening for

receiving the head and for retaining the neck in said opening.

434  
control